



DECLARATION OF PERFORMANCE

DoP No. 002



Manufacturer's Declaration of Performance according to the building products Directive

(Directive 305/2011/EEC of 24th April 2011 for building products)

1. Identification code:

PANEL MADE OF WOOD CHIPS BONDED TOGETHER WITH FIRE-RETARDANT RESIN AND MELAMINE FACED WITH DECORATIVE PAPERS

2. Product brands:

MELAMINE FACED, FIRE-RESISTANT, ECOLOGICAL PANEL®

3. Intended use:

**10 mm TO 28 mm THICK MELAMINE FACED ECOLOGICAL PANEL FOR INDOOR USE
AND FOR GENERAL PURPOSE AS NON-STRUCTURAL COMPONENT AND FOR USE IN DRY CONDITIONS (P1)
WALL / CEILING COATING, NOT IN TOUCH WITH ANY SUPPORT
FLOOR COATING leant**

4. Manufacturer:

GRUPPO MAURO SAVIOLA srl – Plant: V.le Lombardia 29 – 46019 Viadana (MN)

5. Distributed by:

GRUPPO MAURO SAVIOLA srl – V.le Lombardia 29 – 46019 Viadana (MN)

6. Assessment and verification of constancy of performance of the building product:

System 1 according to EN 13986 standard

7. Name of the notified test laboratory that issued the Certificate of Conformity:

LAPI S.p.A. n° 0987 – Laboratorio Prevenzione Incendi S.p.A. – Via della Quercia, 11 – 59100 Prato

Certificate		of assessment and verification of constancy of performance of the Product 0987- cpd 002
--------------------	--	------------------------------------------------------------------------------------------------

8. Not applicable

9. Stated performance

Key Characteristics	Performance	Harmonised Standard			
European Reaction to Fire Classification system (Euroclass)	B-s1, d0 – B_{fl} – s1		EN 13501-1	EN 13986	
Bending Strength	N/mm²		EN 310		
					> 10 to 13 mm - 12.5
					> 13 to 20 mm - 11.5
					> 20 to 25 mm - 10
Tensile Strength	N/mm²		EN 319		
				> 25 to 28 mm - 8.5	
				> 10 to 13 mm - 0.28	
				> 13 to 20 mm - 0.24	
Formaldehyde Release	Class E 1		EN 120		
				> 20 to 25 mm - 0.20	
				> 25 to 28 mm - 0.17	

10. The panel identified under point 3. meets the stated performance according to point 9.

Viadana, 09/06/2014

Quality Manager
Angelo Sarzi