

# ALPLUS

Hanging bench












FREZZA



## TECHNICAL DATA

design Marco Zito

hanging desk system	the structure consists of two legs and a perimeter frame on three sides. Two extruded aluminium profiles, of the same dimensions and characteristics as the frame, are attached to the perimeter frame on one side and under the top of the service cabinet (for the low cabinet) or under the intermediate shelf (for the high cabinet) to provide additional stability.									
structure	<p><u>leg</u>: shaped in die-cast aluminium with an epoxy powder-coated embossed finish. The upper part is fitted with an insert for attachment to the perimeter frame. The leg is equipped with an adjustable polyethylene coated metal foot allowing +10 mm adjustment for floor levelling.</p> <p><u>perimeter frame</u>: made of extruded aluminium painted with epoxy powders with an embossed finish profiles, equipped with an internal groove for attaching the leg insert. The reinforcing beams, arranged along the depth, are fixed to the structure with barrels and grains. Profiles and reinforcing beams are equipped on the inside with a groove for attaching accessories if required.</p>									
top	<p><u>melamine</u>: made of 18-mm thick chipboard (density 720 kg/m<sup>3</sup>, formaldehyde emission compliant with EU Regulation 2023/1464 and EPA TSCA Title VI), faced with anti-reflex melamine resins and edged with ABS (2 mm thick with rounded edges). The top is assembled to the structure by means of galvanised brackets fixed to the top with metric screws and to the beams of the structure with screws and hammer nuts.</p>									
service unit	<p><u>structure</u>: made of 18 mm thick chipboard panels ( density 720 kg/m<sup>3</sup>, formaldehyde emission compliant with EU Regulation 2023/1464 and EPA TSCA Title VI ), faced with anti-reflex melamine resins and edged with ABS (2 mm thick with rounded edges on visible sides). The internal space is divided into 2 compartments: a 14"1/8 compartment with door, and a 30"3/4 open compartment. Available in two heights: 15" and 30"1/4.</p> <p><u>door</u>: made of 18 mm thick chipboard panel (density 720 kg/m<sup>3</sup>, formaldehyde emission compliant with EU Regulation 2023/1464 and EPA TSCA Title VI), faced with anti-reflex melamine resins and edged with ABS (2 mm thick with rounded edges on visible sides). The hinges are made of steel with 110° opening, equipped with a soft-closing device to soften the door closure. The door is equipped with a push-pull opening mechanism.</p>									
hanging bench dimensions	<table><thead><tr><th>W</th><th>D</th><th>H</th></tr></thead><tbody><tr><td>55"1/8</td><td>63"</td><td>29"1/2</td></tr><tr><td>63"</td><td>63"</td><td>29"1/2</td></tr></tbody></table>	W	D	H	55"1/8	63"	29"1/2	63"	63"	29"1/2
W	D	H								
55"1/8	63"	29"1/2								
63"	63"	29"1/2								

	70"7/8	63"	29"1/2
Service units without structure dimensions	W	D	H
	47"1/4	17"3/8	15"
	47"1/4	17"3/8	30"1/4
structure finish	<b>aluminium</b>		
	 ZGBI White embossed painted RAL 9010	 ZGTR Dove embossed painted	 ZGNE Black embossed painted RAL 9005
top finish	<b>melamine</b>		
	 MBI White	 MTR Dove	 MCE Concrete
	 MOB Light elm	 MRO Oak	 MNC Walnut
	 MFN Black ash	 MNV Black velvet	

## OPTIONALS

1. screen	<p><b>melamine:</b> made of 25 mm thick chipboard (density 720 kg/m<sup>3</sup>, formaldehyde emission compliant with EU Regulation 2023/1464 and EPA TSCA Title VI), faced with anti-reflex melamine resins and edged with ABS (2 mm thick with rounded edges).</p> <p><b>fabric:</b> consisting of a 18 mm thick chipboard panel faced with melamine resins, onto which a cushion of adhesive polyethylene foam (density 40 kg/ m<sup>3</sup>) is glued on both sides. The panel is covered with a layer of flame-retardant fabric or eco-leather. The total thickness of the screen is 3 cm.</p> <p>Both screens, in order to be mounted, feature 2 holes (Ø 1/2", D. 7"1/8) on the lower side, which accommodate a vertical support that is anchored to a plate (W. 15"7/8 D. 1"5/8 th. 1/8") fixed underneath the surface with metric screws.</p>
2. top access	<p><b>metal:</b> made of anodised or epoxy-painted extruded aluminium profiles with two ABS closing elements. The upper part includes an extruded or epoxy-painted aluminium door with a dust cover profile at the outlet. The door is hinged to open on one side only. The maximum door opening is 90°. W. 12"1/2 D. 4"3/4 H. 1".</p>
3. cable tray for top access	<p>made of 1 mm thick, U-shaped, epoxy powder-coated steel sheet. The tray interlocks with the top access frame and is fitted with holes on the lower side that can be used for attaching multiple-plug sockets (by means of screws or clamps, not included) or for earthing (by screwing the cable lug for earthing with screw and bolt, not included). W. 11"3/8 D. 3"3/4 H. 4".</p>
4. height-adjustable cable tray (H. 12,5 ÷ 15,4 cm)	<p>made of 1 mm thick epoxy-powder coated steel sheet, open on the sides so that cables can be routed to the adjacent workstations. On the lower side, there are 4 holes (Ø 21"5/8) that allow cables to be routed to the ground and other holes for attaching multiple-plug sockets (by means of screws or clamps - not included) or for earthing (by screwing the cable lug to the ground with a screw and bolt - not included). Each side is equipped with two sets of slots with a 5/8" interaxis, which are used for attaching the supporting brackets and allows them to be adjusted in height. The supporting brackets are made of 1.5-mm-thick epoxy-powder-coated steel sheet and are attached to the beam's slots. Side end caps, made of 1 mm thick epoxy powder-coated steel sheet, are available on request to be attached to the tray.</p> <p>Tray- top distance: 4"7/8 ÷ 6"1/8 (depending on adjustment) Variable W. D. 13"3/8 H. 3"</p>
electrification	<p>the desk can be equipped with the following electrification: VERSATEK (please refer to the electrification section for more specifications).</p>


## ABACO | Hanging bench

Melamine top




## ABACUS | Hanging bench

Cabinet with 1 door and open unit  
H. 15"




Cabinet with 1 door and open unit  
H. 30"1/4




## ABACUS | OPTIONALS

1. screen




Melamine




fabric

2. top access



metal

3. cable tray for top access



4. height-adjustable cable tray  
(H. 4"7/8 ÷ 6")

