



DEVA

Deva - Meeting chair



TECHNICAL DETAILS

backrest	available in a medium version and in the following configurations: Mesh: tubular steel backrest covered with visible stretch mesh. Fabric: padded in polyurethane foam and upholstered in fabric, eco-leather or leather. All types of backrests are equipped with a height-adjustable lumbar support (70 mm), that allows customisation of the contact between the backrest and the user's back, particularly in the lower back area, following the natural curves of the spine. 
seat	12 mm-thick beech plywood with polyurethane foam padding.
armrests	- 2D adjustable (height 90 mm, depth 40 mm) in soft touch nylon with a black plastic finish. - 3D adjustable (height 90 mm, depth 40 mm and rotation +/- 10°) in soft touch nylon, with aluminium support. 

device	synchronised self-calibrating device with 3-position adjustment (tilting angles: position 0: 0,4° backrest, 1,5° seat; position 1: 7,9° backrest, 0,76° seat; position 2: 16,9° backrest; 3,3° seat) and anti-shock backrest release system. This mechanism allows automatic adaptation to the weight of the user without requiring any operation. The backrest tilt resistance is directly proportional to the weight exerted on the seat.  Lever on the right, to adjust the seat height
device	synchronised self-calibrating device with 3-position adjustment with seat depth adjustment (70 mm) (tilting angles: position 0: 0,4° backrest, 1,5° seat; position 1: 7,9° backrest, 0,76° seat; position 2: 16,9° backrest; 3,3° seat) and anti-shock backrest release system. This mechanism allows automatic adaptation to the weight of the user without requiring any operation. The backrest tilt resistance is directly proportional to the weight exerted on the seat. The seat depth adjustment ensures an adequate support surface for people of different heights and builds. By sliding the seat backwards and forwards, the thigh support base can be changed at will, providing a dynamic adjustment of the leg position.  Lever on the right, to adjust the seat height Lever on the left, to adjust the seat depth
height adjustment	by gas lift. It allows an excursion of 13 cm.
base	5-star base in nylon or die-cast polished aluminium. Self-locking, dual-tread, rubbered, swivel castors, for hard floors Ø 65 mm, as standard.
ergonomics	Deva is equipped with the necessary mechanisms for proper and comfortable use, even for prolonged periods, as long as the following conditions are met: the standard sitting position requires maintaining angles of 90° between torso and thigh, between thigh and leg, and between leg and foot. These last two angles are essential so that the foot, resting completely on the surface below, discharges part of the weight of the lower limb onto it, preventing excessive compression on the back thigh surface and promoting blood circulation to the heart. 
base finishes	Polished aluminium Black nylon
mesh	**Cat. E** Polo RPRO RPBI RPG1 RPGR RPRE RPZ0 **Cat. N** Spin S1V1 S1B8 S1R0 S1V0 S1G4 S1G0 S1G2 S1NE

fabrics

Cat. V

Volley FR

R6NE

Cat. B

Bondai

TBB2 TBB1 TBB6 TBB4 TBV2 TBR2 TBR1
TBMN TBR3 TBR0 TBV1 TBV4 TBV0 TBB0
TBM1 TBBE TBGC TBAV TBG0 TBZ0

Cat. H

Madrid 3D

T3M0 T3V0 T3V2 T3B2 T3V4 T3M3 T3B3

Boss FR (eco-leather)

T4BI T4M5 T4M8 T4M6 T4M4 T4M7 T4M3
T4M0 T4M1 T4M2 T4V0 T4G0 T4G1 T4R1
T4R0 T4B0 T4B1 T4V4 T4V1 T4NE

Cat. D

King Flex

XFML XFB2 XFAZ XFH6 XFB4 XFBX XFRM
XFZC XFM0 XFS2 XFYD XFYS XFV1 XFVM
XFB0 XFGC XFGS XFJ1 XFM1 XFCD XFZ0

Time

S6G2 S6V0 S6R2 S6R1 S6R6 S6R3 S6R5
S6B7 S6B1 S6B0 S6B4 S6V1 S6V3 S6V4
S6M2 S6M1 S6M0 S6G0 S6B5 S6G1

Skill (eco-leather)

PGM3 PGTR PGCD PGTA PGR1 PGCG PGBZ
PGGB PGVC PGM2 PGNE

Cat. F

Step

STX2 STZ9 STBS STE1 STBS STVU STE4
STE3 STE2 STNE

Chili

S0G6 S0G2 S0G3 S0M3 S0V2 S0R0 S0R4
S0RA S0R7 S0R2 S0B9 S0B8 S0V5 S0V6
S0V7 S0NE

Silvertex

SBR7 SBV1 SBR3 SBR4 SBR5 SBR6 SBB7
SBB3 SBB6 SBG1 SBBI SBM2 SBV4 SBV6
SBV3 SBG6

Valencia (eco-leather)

SWR6 SWBI SWV7 SWRA SWR8 SWR3 SWR2
SWB8 SWG4 SWB9 SWB2 SWM6 SWG0 SWG8
SWG7 SWG1

Jet

JTW2 JTW3 JTH2 JTGM JTYF JT1R JTRG
JTO1 JTR1 JTVM JT07 JTVI JTG3 JTV7
JTC1 JTV8 JTB3 JTZ6 JTM2 JTZ0

Magnum Bio Base (eco-leather)

T5G7 T5B0 T5B6 T5B2 T5B5 T5R4 T5R6
T5V3 T5G1 T5M6 T5M5 T5G4 T5M3 T5V8
T5NE

Connect

T6G0 T6G1 T6G2 T6R0 T6R1 T6R2 T6V5
T6V6 T6B6 T6NE

Rivet

T7B1 T7B4 T7B2 T7R6 T7R0 T7R1 T7R2
T7R3 T7V0 T7V5 T7V4 T7V3 T7G3 T7G1
T7G4 T7G7

Era

T8R0 T8R1 T8R2 T8R3 T8R9 T8V8 T8V2
T8V5 T8V6 T8V0 T8G1 T8G4 T8BA T8BB
T8G6 T8NE

Go Check

T9B7 T9B8 T9B9 T9R5 T9R6 T9R7 T9V0
T9V2 T9V3 T9G0 T9G2 T9G4

Cat. I

Buffalo leather

PWBI PWRE PWBC PWGS PWMS PWNE

Cat. P


Leather

URBI URBE URBC URGR URGS URVS URMR
URMC UROC URYE UROR URRE URBS URVE
URNE


ABACUS

Mesh Meeting


3-position synchronised self-calibrating device.
With 2D armrests.




3-position synchronised self-calibrating device + seat depth adjustment.
With 2D armrests.




3-position synchronised self-calibrating device.
With 3D armrests.




3-position synchronised self-calibrating device + seat depth adjustment.
With 3D armrests.



3-position synchronised self-calibrating device.
Without armrests.




3-position synchronised self-calibrating device + seat depth adjustment.
Without armrests.




Fabric Meeting


3-position synchronised self-calibrating device.
With 2D armrests.




3-position synchronised self-calibrating device + seat depth adjustment.
With 2D armrests.




3-position synchronised self-calibrating device.
With 3D armrests.



3-position synchronised self-calibrating device + seat depth adjustment.
With 3D armrests.



3-position synchronised self-calibrating device.
Without armrests.



3-position synchronised self-calibrating device + seat depth adjustment.
Without armrests.

