

POP ACE

High table

fREZA



TECHNICAL DATA

structure

leg: made of a 1.5 mm thick, square-section bar (W. 1" 3/4 D. 1" 3/4) with rounded edges, bent and welded to form two uprights and a beam. The uprights are inclined by 97°. 2 mm thick steel U-shaped brackets (2 for 31" 1/2 deep tables and 4 for 49" 1/4 deep tables) are attached to the beam for connecting the longitudinal beams. On the lower part there is a supporting beam (made from the same section bar as the leg) welded to both uprights, equipped with slots on the inner side for connecting the lower reinforcing beams. All metal parts are painted with powders with an embossed finish. On the inside of the upright, at the lower end of the leg, a 4 mm thick steel plate is welded with a central hole for PE feet (Ø 1" 3/8). The feet allow for an adjustment of + 10 mm for levelling.

longitudinal beams: each top is supported by 2 beams for 31" 1/2 depth and 4 for 49" 1/4 depth, made of 1.5 mm thick steel section bars (W. 1" 3/4 D. 1" 3/4) with rounded edges, fixed to the leg brackets. All metal parts are painted with powders with an embossed finish.

supporting beams: made of 1.5 mm thick, square-section steel bars (W. 1" 3/4 D. 1" 3/4) with rounded edges and equipped with hooks at the ends. They are fixed on one side to the slots of the metal leg's supporting beam. All metal parts are powder-coated with an embossed finish.

top

melamine: made of 18 mm thick chipboard (density 720 kg/m³, formaldehyde emission compliant with EU Regulation 2023/1464 and EPA TSCA Title VI), faced with anti-reflex melamine resins and edged with ABS (2 mm thick with rounded edges) with matching / colour-contrasting edge. The top is fixed to the brackets with screws. The brackets create a gap of 5.5 mm between the top and the leg beam.

high table dimensions

	W	D	H		W	D	H
	47"1/4	31"1/2	41"3/8		55"1/8	49"1/4	41"3/8
	55"1/8	31"1/2	41"3/8		63"	49"1/4	41"3/8
	63"	31"1/2	41"3/8		70"7/8	49"1/4	41"3/8
	70"7/8	31"1/2	41"3/8		78"3/4	49"1/4	41"3/8

standard finishes for metal leg and beam

metal



ZGBI V White embossed
painted RAL 9010



ZGAS Aluminium
embossed painted RAL
9006



ZGNE Black embossed
painted RAL 9005


special finishes for metal leg and beam	metal leg* (special finishes only for leg)					
		ZGV0 Maize yellow embossed painted RAL 1006		ZGR0 Titian red embossed painted RAL 050 50 60		ZGB0 Gentle blue embossed painted RAL 250 60 15
		ZGB1 LED blue embossed painted RAL 260 40 45		ZGG0 Pebble grey embossed painted RAL 7032		ZGG5 Green grey embossed painted RAL 7009
metal beam (beam finish for legs in special finish)						
		ZGAS Aluminium embossed painted RAL 9006				
top finish	melamine					
		MBI White		MWP Pearl white		MTR Dove
		MCE Concrete		MOB Light elm		MRO Oak
		MNC Walnut		MFN Black ash		MNV Velvet black
melamine with colour-contrasting edge						
		GMBI – White with green grey edge		NMBI – White with black edge		BMOB – Light elm with white edge
		GMOB – Light elm with green grey edge		NMOB – Light elm with black edge		GMNC – Walnut with green grey edge
		NMNC – Walnut with black edge		GMNV – Black velvet with green grey edge		

OPTIONALS


1. top access	metal : made of a powder-coated aluminium frame and two self-extinguishing thermopolymer closing elements. The upper part includes a painted aluminium door which can open on either side by means of a tilting movement. On both sides there is an dust cover profile. Dimensions: W. 12"1/2 D. 5"7/8 H. 1"
2. cable tray for top access	made of 1 mm thick, U-shaped, epoxy powder-coated steel sheet. The tray interlocks with the top access frame and is fitted with holes on the lower side that can be used for attaching multiple-plug sockets (by means of screws or clamps, not included) or for earthing (by screwing the cable lug for earthing with screw and bolt, not included). W. 11"3/8 D. 4"7/8 H. 3"7/8
3. bag holder	made of a 1.5 mm thick steel sheet, painted with powders with an embossed finish and shaped to rest on the supporting beams. To be used only on tables with a depth of 49"1/4. W. 19" 5/8 D. 19" 5/8 H. 1" 3/4
4. bag hook	made of a 1.5 mm thick steel sheet, folded and epoxy powder-coated with an embossed finish. At the top it has a Ø 5 mm hole for under-top fixing with wooden screws. W. 1"3/4 D. 2"5/8 H. 2"1/2
5. vertical cable duct	consisting of a 3 mm thick folded steel sheet base (W. 5' 7/8 D. 5' 7/8 H. 1/4') painted with powders, and a series of rectangular plastic elements (L. 2"1/2 D. 1"5/8 H. 1"1/8) joined together to convey the cables to the top. At the end there is an element for fixing to the top (using self-tapping wood screws). L. 2"1/2 D. 1"5/8 H. 55"1/8
electrification	the desk can be equipped with the following electrification: NETBOX POINT – VERSATEK – ALUPOWER – LID FOR CABLE MANAGEMENT (please refer to the electrification section for more specifications).

ABACUS | High tables

High table H. 41"3/8 - D. 31"1/2




High table H. 41"3/8 - D. 49"1/4



ABACUS | Optionals


1. top access



2. cable tray for top access



3. bag holder



4. bag hook



5. vertical cable duct

