

POP EASY

Meeting table

FREZZA



TECHNICAL DATA

structure

leg: made of a 1.5 mm thick square-section steel bar (W. 1" 3/4 D. 1" 3/4) with rounded edges. The bar is laser-cut, bent and welded, forming the two uprights and beam. Two U-shaped brackets, made of 2 mm thick steel sheet, are welded onto the leg beam. These brackets are used to attach the longitudinal beams and to support the worktop. The lower ends of the legs are equipped with polyethylene-coated steel feet (Ø 1"3/4), screwed onto polyethylene tips that are press-fitted into the lower part of the leg. The feet allow an adjustment of + 10 mm for floor levelling. All metal parts are painted with powders with an embossed finish.

longitudinal beams: each worktop is supported by two beams made of 1.5-mm-thick steel section bars (W. 1" 3/4 D. 1" 3/4) with rounded edges, attached to the leg brackets, powder coated with an embossed finish.

intermediate leg: consisting of a steel section bar beam with a 1,5 mm thick 80x40 rectangular cross-section with rounded edges, closed at the ends by plastic caps. 2 uprights are screwed under the frame by means of a 4 mm thick steel plate, made of 1.5 mm thick square-section steel bars (W. 1" 3/4 D. 1" 3/4) with radiused edges. On the inner side of the uprights there are slots for the application of an optional inspectable carter with the purpose of concealing the cable descent. A pair of "U" brackets made of 2 mm thick steel sheet are welded on the beam, which is used to attach the longitudinal beams and support the worktops. The lower ends of the uprights are equipped with feet (Ø 1" 3/4) made of polyethylene-coated steel, screwed onto polyethylene tips that are press-fitted into the base. The feet allow ±10 mm adjustment for floor levelling. All metal parts are painted with powders with an embossed finish.

top




melamine: 18 mm thick chipboard (density 720 kg/m³, formaldehyde emission compliant with EU Regulation 2023/1464 and EPA TSCA Title VI), faced with anti-reflex melamine resins and edged with ABS (2 mm th. with rounded edges) with matching or contrasting edge. The top is equipped with threaded inserts for attachment to the structure and for fixing the screens. The top is fixed with screws to the brackets which create a 5 mm gap between the top and the leg beam. H floor-to-top: 74 cm

painted glass: 10 mm thick, tempered in accordance with EN 12150 standard with flat polished edges, painted on the underside (if the paint is white, extra-clear glass is used). Equipped with steel studs on the lower side of the glass, with threaded holes for fixing it to the structure.

melamine meeting table dimensions	W	D	H	W	D	H
	49"1/4	49"1/4	29"1/8	65"	65"	29"1/8
55"1/8	49"1/4	29"1/8	94"1/2	65"	29"1/8	
63"	49"1/4	29"1/8	110"1/4	65"	29"1/8	
70"7/8	49"1/4	29"1/8	126"	65"	29"1/8	
78"3/4	49"1/4	29"1/8	129"7/8	65"	29"1/8	
86"5/8	49"1/4	29"1/8	141"3/4	65"	29"1/8	
94"1/2	49"1/4	29"1/8				
110"1/4	49"1/4	29"1/8				
126"	49"1/4	29"1/8				
141"3/4	49"1/4	29"1/8				
173"1/4	49"1/4	29"1/8				


glass meeting table dimensions	W	D	H	W	D	H
	49"1/4	49"1/4	29"1/8	65"	65"	29"1/8
86"5/8	49"1/4	29"1/8				










starting/ intermediate and ending meeting table dimensions for composition	W	D	H	W	D	H
	47"1/4	49"1/4	29"1/8	47"1/4	65"	29"1/8
55"1/8	49"1/4	29"1/8	55"1/8	65"	29"1/8	
63"	49"1/4	29"1/8	63"	65"	29"1/8	
70"7/8	49"1/4	29"1/8	65"	65"	29"1/8	
			70"7/8	65"	29"1/8	

standard finishes for metal leg and beam	metal		
	 ZGBI White embossed painted RAL 9010	 ZGAS Aluminium embossed painted RAL 9006	 ZGNE Black embossed painted RAL 9005







special finishes for metal leg and beam	metal leg*(special finishes only for leg)		
	 ZGVO Maize yellow embossed painted RAL 1006	 ZGR0 Titian red embossed painted RAL 050 50 60	 ZGB0 Gentle blue embossed painted RAL 250 60 15
 ZGB1 LED blue embossed painted RAL 260 40 45	 ZGG0 Pebble grey embossed painted RAL 7032	 ZGG5 Green grey embossed painted RAL 7009	

metal beams (beam finish for legs in special finish)

 ZGAS Aluminium embossed painted RAL 9006
--

top finishes	melamine		
	 MBI White	 MWP Pearl white	 MTR Dove
 MCE Concrete	 MOB Light elm	 MRO Oak	
 MNC Walnut	 MFN Black ash	 MNV Velvet black	

melaminico with colour-contrasting edge

 GMBI – White with green grey edge	 NMBI - White with black edge	 BMOB – Light elm with white edge
 GMOB – Light elm with green grey edge	 NMOB – Light elm with black edge	 GMNC – Walnut with green grey edge



NMNC - Walnut with black edge



GMNV - Black velvet with green grey edge

glass



VTBI White painted glass on the lower side




VTNE Black painted glass on the lower side

OPTIONALS

1. top access	metal: made of anodised or powder-coated extruded aluminium with two ABS closing elements. The upper part includes an extruded or painted aluminium door that can be opened on either side. There is a dust cover profile on both sides. W. 12" 1/2 D. 5"1/16 H. 1"
2. cable tray for top access	made of 1 mm thick U-shaped powder-coated steel sheet. The tray interlocks with the top access frame. Fitted with holes on the lower side that can be used for attaching multiple-plug sockets (by means of screws or clamps, not included) or for earthing (by screwing the cable lug for earthing with screw and bolt, not included). W. 11"3/8 D. 3"3/4 H. 3"7/8.
3. removable carter (for intermediate leg)	made of 1 mm thick powder-coated steel plate and fitted with hooks for attachment to the middle of the legs. A space of 1"5/8 remains between the floor and the lower edge of the carter to allow for the passage of cables. The same space is available at the top between the leg beam and the upper edge of the carter. W. 6" 1/2 D. 2" H. 23" 1/4.
4. vertical cable duct	composed of a 3 mm thick folded powder coated steel sheet base (W. 5' 7/8 D. 5' 7/8 H. 1/4') and a series of rectangular plastic elements (W. 2" 1/2 D. 1" 5/8 H. 1" 1/8) joined together to guide the cables to the top. For each vertebra there are 45 elements (H. max. 33" 1/8). At the end there is an element for fixing the vertical cable management to the top (using self-tapping wood screws).
electrification	the desk can be equipped with the following electrification: VERSATEK - ALUPOWER (please refer to the electrification section for more specifications).

ABACUS | Meeting tables


Meeting table – Melamine top
D. 65"/49"1/4



Meeting table – Melamine top
D. 49"1/4




Meeting table – Glass top
D. 65"/49"1/4




Meeting table – Glass top
D. 49"1/4



D. 49"1/4 meeting table




D. 65"/49"1/4 meeting table



Meeting tables for compositions


STARTING

Initial meeting table





INTERMEDIATE

Intermediate meeting table




ENDING

Ending meeting table




ABACUS | Optionals


1. Top access



2. Cable tray for top access



3. pair of removable carters (for intermediate leg)



4. vertical cable duct

